

DESCRIPTION

Total Thickness	EN ISO24346 (EN 428)	mm	0.93
Weight	EN ISO 23997 (EN 430)	g/m ²	200
Width	EN ISO 24341 (EN 426)	cm	100
Length	EN ISO 24341 (EN 426)	m	15
Packaging content		m ²	15
Packaging Weight		kg	3
Article code			17980001

CLASSIFICATION

Fire rating	EN 13501-1	classe	Efl (underlayer alone) Bfl-s1 (with Creation 70 CLic, Creation 55 Clic / Creation 30 Clic / Virtuo 55 Clic / Virtuo 30 Clic / Senso 20 Lock / Rigid 30 Lock)
-------------	------------	--------	---

PERFORMANCE

Impact sound insulation	EN ISO 717-2	dB	16 (with Creation 70 Clic) 15 (with Creation 55 Clic / Creation 30 Clic / Virtuo 55 Clic / Virtuo 30 Clic / Senso 20 Lock / Rigid 30 Lock)
Thermal resistance	EN 12664	m ² K/W	0.023
Compressive Strength	EN ISO 3386 / EN826	kPa	400
Compressive Strength	EN ISO 3386 / EN826	t/m ²	40



This underlay is recommended by Gerflor for the following products :

- CREATION 70 CLIC
- CREATION 55 CLIC
- CREATION 30 CLIC
- VIRTUO 55 CLIC
- VIRTUO 30 CLIC
- SENSO 20 LOCK (For classe 22 use only)
- RIGID 30 LOCK (For classe 22 use only)